

SECTION-B

2. a) A mass of 1.5 kg of air is compressed in a quasi-static process from 1.1 bar to 10 bar according to the law $pV^{1.25} = \text{Constant}$. The initial density of air is 1.2 kg/m^3 . Find the work involved in the compression process. 4
- b) What is the concept of continuum? How density and pressure are defined using this concept? 4
3. Steam enters a nozzle at a pressure of 7 bar and 205°C (*i.e.* initial enthalpy 2850 kJ/kg) leaves at a pressure of 1.5 bar. The initial velocity of steam at the entrance is 40 m/s and exit velocity from the nozzle is 700 m/s . The mass flow rate through the nozzle is 1400 kg/hr . The heat loss from the nozzle is 11705 kJ/hr . Determine the final enthalpy of steam and the nozzle exit area, if the specific volume is $1.24 \text{ m}^3/\text{kg}$. 8
4. a) Prove that the efficiency of an engine working on a reversible cycle depends only on the temperature of source and sink and is independent of the working fluid. 4
- b) Comment on the validity of the statement : All reversible engines operating between the same two thermal reservoirs have the same efficiency. 4
5. a) Define entropy and show that for an irreversible process. 4

$$\int dS > \int \frac{\delta Q}{T}$$

- b) Heat flows from a reservoir at 800 K to another reservoir at 250 K . If entropy change of the hot reservoir is -4 kJ/K , determine the entropy change of the cold reservoir. 4

SECTION-C

6. Derive an expression for efficiency and mean effective pressure of Otto cycle. 8
7. a) Find the moment of inertia of a circle about its diametrical axis. 4
- b) Find the centroid of a quarter of a circle. 4
8. a) Discuss the effect of following alloying elements in steel :
 a) Chromium
 b) Nickel
 c) Tungsten
 d) Sulphur 4
- b) What are ceramics? Explain classification of ceramics. Also write properties and application of ceramics. 4
9. a) Explain briefly, particle-reinforced, fibre-reinforced and structural composite. 4
- b) A diesel engine takes in air at 1 bar and 27°C . The compression and expansion ratios are 18 and 6 respectively. Estimate the quantity of heat energy added, rejected and the efficiency of the cycle. Take $\gamma = 1.4$, $c_p = 1.005 \text{ kJ/kg} - \text{K}$, and $c_v = 0.717 \text{ kJ/kg} - \text{K}$. 4